
Steering Wheel Control Interface

To suit Ford & Mazda

ASFO7C

Steering wheel controls **Reverse camera***

*If originally fitted. Also provides park brake, reverse and speed signal (VSS) outputs.



Vehicle Fitment

This interface suits the vehicles below.

Vehicle	Year
Ford Ecosport	2013 - 2017
Ford Focus	2012 - 2014
Ford Focus	2015 - 2018
Ford Kuga	2013 onwards
Ford Ranger	2012 - 2015
Ford Ranger (MKII)	2015 - 2018
Ford Transit Custom	2013 - 2017
Ford Transit VO	2014 - 2017
Mazda BT-50	2012 - 2018
Mazda BT-50 Alpine 7"	2018 - 2019

Before you start: read this manual in full. Installation needs technical knowledge. Your head unit must be SWC compatible, and steering wheel functions may differ from the factory functions. Always disconnect the module before changing any DIP switch.

Installation Steps


Complete these four steps in order to finish the installation.

1	2	3	4
Set vehicle DIP switches	Set stereo DIP switches	Connect the interface	Set up your head unit

1 Set the vehicle DIP switches (1 to 8)

Disconnect the module before changing any DIP switch. DIP switch: ON OFF


ALL VEHICLES



Switches 5 and 6 ON, all others OFF

2 Set the stereo DIP switches (1 to 4)

Set switches 1 to 4 for your head unit brand.



Not listed? Use **Program** and set up SWC Learning in your head unit (see Step 4).


3 Connect the interface

Connect the vehicle plug and ISO plugs, then use the SWC connection that matches your head unit. Most head units only need one.

Your head unit	Connect
Aerpro AM905D, AM1005D, Pioneer DMH-AP6650BT	**8-pin connector and 3.5mm jack**
Aerpro (other), Alpine, Pioneer, Sony, Nakamichi	**3.5mm jack** to the head unit SWC input
Kenwood, JVC	**Key 1 lead** to the SWC wire (SWC function only)
Android head units, Nakamichi Android, Alpine INE-AW409S, INE-AX809	**8-pin connector** (or Key 1, Key 2 and GND)
No plug-in SWC input	**Key 1 lead**, plus Key 2 and GND if needed

Kenwood 8-pin: a separate Kenwood adaptor is needed for UART functionality.

Step 3 wiring diagram



4 Set up your head unit

Find your head unit brand below and follow the setup for it.

Head unit	Setup
Aerpro Incl. AM905D, AM1005D, AM9X, AM10X	• **3.5mm jack:** set stereo DIP switches to 1-ON, 2-ON, 3-OFF, 4-OFF. Go to Settings > Steering Wheel Control > With Adapter. • **8-pin adaptor:** reset the unit > select Hiworld > select vehicle type > program SWC as shown on screen. Factory vehicle info will display.
Alpine, JVC, Kenwood	Work straight away, no setup needed.
Nakamichi	Presets: NA3615 (W7, W9, WX, M9, MX), NA3510-M7, NA3625 (W6, WUX).
Pioneer Other models	Settings > Steering Wheel Control > With Adapter.
Pioneer Incl. DMH-AP6650BT	• **3.5mm jack:** set stereo DIP switches to 1-ON, 2-ON, 3-OFF, 4-OFF. Go to Settings > Steering Wheel Control > With Adapter. • **8-pin adaptor:** reset the unit > select Hiworld > select vehicle type > program SWC as shown on screen. Check the Pioneer website for compatibility.
Sony	Settings > General > Steering Control > Preset. If Preset doesn't work, set stereo DIP switches to 1-OFF, 2-ON, 3-ON, 4-OFF and use Custom.

Head unit	Setup
Android head units Incl. Aerpro AM1205D, Alpine INE-AW409S, INE-AX809, Nakamichi Android	Connect the 8-pin (CANBUS) plug, or Key 1, Key 2 and GND. • **With CANBUS:** set stereo DIP switches to Android > Factory Settings. Alpine password 1967. Nakamichi password 1948, then select Hiworld as provider and choose vehicle type. • **Without CANBUS:** set stereo DIP switches to Program > select SWC Learning in the head unit menu.

Time Setting (If applicable) (Ford models)

1. **Enter setup mode:** press and hold the Voice button on the steering wheel for 15 seconds. This lets you set the clock.
2. **Set the time:** use the Volume Up and Down buttons to change the value. Press Next to move through hour, minutes, date, month and year.
3. **Exit:** press Next after setting the year to leave setup mode.

Time & Amplifier Setting (If applicable) (Mazda models)

1. **Enter setup mode:** press and hold the MODE / Pick-Up button on the steering wheel for 15 seconds. This lets you set the clock and the factory amplifier output level.
2. **Set the time:** use the Previous and Next buttons.
3. **Set the amplifier output:** use the Volume Up and Down buttons to raise or lower the factory amplifier level.
4. **Exit:** setup mode closes automatically after 20 seconds without a button press.

Final Check

With the ignition ON, check everything works before refitting the dash.

- ☐ Each steering wheel button works
- ☐ Volume works through the factory amplifier (if fitted)
- ☐ Reverse camera shows in reverse (if fitted)
- ☐ Radio reception is clear
- ☐ USB and AUX play (if fitted)

Scan to view ASFO7C on aerpro.com
aerpro.com/asfo7c

Technical Support

Need help setting up or using your Aerpro product? Call Aerpro Support Australia on **03 8587 8889**, Monday to Friday, 9am to 5pm AEST. Download a digital copy of this manual and other Aerpro manuals and software at **aerpro.com**.